



DECK CHARGER: LC-333 792272

Power supply AC90-260V 50/60Hz	Power consumption 50W	Output: DC 12V Maximum 2A x2
Charging time 1.5hrs	weight 600g	IP20



INTRINSICALLY SAFE RESCUE FLASHLIGHT:
EX-2380 (RECHARGEABLE) 792267

II 2G Ex ib op is IIC T4 Gb II 2D Ex ib op is IIIC T130°C Db	Source Lumens High : 210 lm Medium : 126 lm Low : 53 lm Strobe light : 210 lm S.O.S : 210 lm	Effective Lumens High : 125 lm Medium : 75 lm Low : 32 lm Strobe light : 125 lm S.O.S : 125 lm
LED 7.4V, 3W High, Medium, Low, Strobe light & S.O.S	Beam distance 120m	Impact resistance 1.8m
Area of classification (gases) Zones 1 & 2 Gas Groups IIA, IIB & IIC	Area of classification (dusts) Zones 21 & 22 Dust Groups IIIA, IIIB & IIIC	Temp. classification (gases) T4
Max. surface temp. (dusts) 130°C	Ambient temperature -20°C to +40°C	SPOT
Rechargeable Lithium-Ion 7.4V 2500 mAh	Maintain (hrs) High : 10 Medium : 17 Low : 42 Strobe light : 22 S.O.S : 20	Compatible charger LC-333
weight 362g	IP66	

RECHARGEABLE

INTRINSICALLY SAFE
HEAD LIGHT: EX-2780
(RECHARGEABLE)



headband included

I M2 Ex ib I Mb II 2G Ex ib op is IIC T4 Gb II 2D Ex ib IIIC T135°C Db	Mining	Source Lumens High : 193 lm Low : 64 lm Flood : 210 lm Strobe light : 193 lm	Effective Lumens High : 139 lm Low : 46 lm Flood : 65 lm Strobe light : 139 lm	LED 3.7V, 1.8W High, Low, Flood mode & Strobe light	Beam distance 62m	Impact resistance 2m
Area of classification (gases) Zones 1 & 2 Gas Groups IIA, IIB & IIC	Area of classification (dusts) Zones 21 & 22 Dust Groups IIIA, IIIB & IIIC	Temp. classification (gases) T4	Max. surface temp. (dusts) 135°C	Ambient temperature -20°C to +40°C	SPOT/ FLOOD	Weight without headband 165g
Rechargeable Lithium-Ion 4.2V, 1600 mAh	Compatible charger LC-2780	Charging time 3.5hrs	Charger input AC100-240V, DC12-24V	Charger output DV 5V 2A (10W)	IP66	



INTRINSICALLY SAFE SAFETY
HAND LAMP: AT-1380 (RECHARGEABLE)



Ex II 2G Ex ib op is IIC T4 Gb
II 2D Ex ib IIIC T135°C Db IP66

Source Lumens 446 lm	Effective Lumens 242 lm	LED 3.7-4.2V, 4W	Beam distance 191m
Impact resistance 1.5m	Area of classification (gases) Zones 1 & 2 Gas Groups IIA, IIB & IIC	Area of classification (dusts) Zones 21 & 22 Dust Groups IIIA, IIIB & IIIC	Temp. classification (gases) T4
		Max. surface temp. (dusts) 135°C	Ambient temperature -20°C to +40°C
SPOT	Light duration Up to 19.3 hrs	Life time 100000hrs	Rechargeable B-250R-A, Lithium-Ion 3.7-4.2V, 7.5Ah
	Battery pack life Up to 500 recharge cycles	Compatible charger LC-250	without shoulder strap 1.196kg
			IP66

RECHARGEABLE



SAFETY HAND LAMP CHARGER UNIT:
LC-250 330609

Power supply AC90-260V 50/60Hz	Power consumption 10W	Output: DC 10V Maximum 800mA Maximum
Charging time 12.5hrs	weight 672g	IP20



INTRINSICALLY SAFE SAFETY HAND LAMP:
EX-250RL (RECHARGEABLE) 330608L

Ex II 2G Ex ib op is IIC T4 Gb
II 2D Ex ib IIIC T135°C Db IP66

Source Lumens **106 lm** Effective Lumens **50 lm** **LED** 4V, 1W

Beam distance 50m	Impact resistance 1.5m	Area of classification (gases) Zones 1 & 2 Gas Groups IIA, IIB & IIC	Area of classification (dusts) Zones 21 & 22 Dust Groups IIIA, IIIB & IIIC	Temp. classification (gases) T4
Max. surface temp. (dusts) 135°C	Ambient temperature -20°C to +40°C	SPOT	Light duration Up to 21hrs	Life time 25000hrs
Rechargeable Lithium-Ion 3.7V, 7.5Ah	Battery pack life Up to 500 recharge cycles	Compatible charger LC-250	without shoulder strap 1.145kg	IP66



EXPLOSION-PROOF SAFETY HAND LAMP
STACKING STAND WITH 6 X AT-1380:
FS-106 HAND LAMP HOLDER WITH "SNAP-IN/SNAP-OUT" FUNCTION

Hand lamp holder material: Polypropylene (PP)	Flood light stand material: 304 Stainless steel with anti-static coating	Length x width x height: 370 x 510 x 522 mm
Weight-carrying in work: 1 x stand + 6 x AT-1380 hand lamp w batteries 14.60kg	Stand net weight: 7.00kg	

TRIPOD
STAND FOR
STACKING STAND:
B-400

Material: 304 Stainless steel with anti-static coating	Rotating angle: 360°
Unfolded height: 1348 mm	Net weight: 5.30kg

Suitable for:
FS-004, FS-006,
FS-104, FS-106
Stacking Stand

SAFETY HAND LAMP
LINE DECK CHARGER: LC-550

Apparatus standards: 2014/34/EU Low Voltage Directive 2014/30/EU Electromagnetic Compatibility Directive		Enclosure Material: Polypropylene (PP)
Power supply: AC90-260V 50/60Hz	Power consumption: 10W x 6	Output per each charge port: 10V/DC max. 800mA max.
	Charging time: 12.5hrs	IP20
	Cable length: 2M	Stand net weight: 3.75kg
	Length x width x height: 871 x 205 x 150 mm	



SAFETY HAND LAMP LINE DECK CHARGER: LC-450

Apparatus standards: 2014/34/EU Low Voltage Directive 2014/30/EU Electromagnetic Compatibility Directive		Enclosure Material: Polypropylene (PP)	Power supply: AC90-260V 50/60Hz	Power consumption: 10W x 4
Output per each charge port: 10V/DC max. 800mA max.	Charging time: 12.5hrs			
IP20	Length x width x height: 596 x 205 x 150 mm			
Cable length: 2M	Stand net weight: 2.57kg			

EXPLOSION-PROOF
SAFETY HAND LAMP STACKING STAND
WITH 4 X AT-1380: FS-104

Hand lamp holder material: Polypropylene (PP)	Flood light stand material: 304 Stainless steel with anti-static coating	Length x width x height: 370 x 380 x 522 mm
Weight-carrying in work: 1 x stand + 4 x AT-1380 hand lamp w batteries 10.00kg	Stand net weight: 5.00kg	



**Information about the AT-1380, please refer to Rechargeable Series Page 2.